



Features:

- Aluminium extrusion with anodized or electrostatic paint finish as standard.
- Average weight per meter approx 4.5 Kg/m.
- Frosted polycarbonate diffuser, factory fitted or choice of a roll for continuous lengths up to 50 meters.
- Clean-cut magnetic end caps, screwless.
- Seamless connect joining system, factory fitted plug and play system for electrical connections.
- Suitable for surface, trimless recessed and suspended (Field adjustable suspension wires) installations.
- Joiner options (Lit corner 90°./cross 90°/tee 90°/straight 180°, customised bend).
- Integral driver.
- Incremental length 50mm.
- Lumen maintenance up to 50,000hrs (L90 B10 @35°).

| ITEMCODE | WATTAGE | COLOR TEMP | DIM. (mm) | LED LUMEN |
|-----------|---------|------------|----------------|-----------|
| 544425 IP | 25W | 3000K | 1000 X 55 X 70 | 2300LM/M |
| 544425 IP | 25W | 4000K | 1000 X 55 X 70 | 2400LM/M |



Applications

Offices, hospitality, schools, hospitals, malls, accent lighting, retails, large indoor open areas.

Options

- **Dimming:** DALI and DSI dimming
1-10V dimming
- **CRI 95+**
- **Color Temperatures :** 3000K, 4000K and 5000K
- **Individual luminaire or continuous runs**
- **Customised wattages**
- **Emergency modules**
- **Bends :**

